



C&Lube Co., Ltd. since 1995
tel.82-52-239-5189 fax.82-52-239-5105

Special Lubricants
Custom Made Oils & Greases

182, Hwasan-ro, Onsan-up, Ulju-kun, Ulsan, KOREA, 45009
www.cnlube.co.kr, e-mail : adm@cnlube.co.kr

Certification of Analysis

Customer INDIVIDUAL ENTREPRENUER **Date** 12-Aug-25
Product EAGLE PAO FE SYNTHETIC 5W30 API-SP RC, **Lot. No.** 25081125
ACEA C2

Test Item	Test Method	Spec.	Results
Appearance	Visual	Clear & Bright	C & B
Density(15°C), kg/m ³	ASTM D 287	Report	845,6
Kinematic Viscosity(100°C), mm ² /s	ASTM D 445	9.3 ~ 12.5	10,06
Viscosity Index	ASTM D 2270	85 min.	180
Apparent Viscosity(-30°C), Pa.S	ASTM D 5293	6.6 max.	3,55
Flash Point, °C	ASTM D 92	190 min.	226
Pour Point, °C	ASTM D 97	-30 max.	-42

This data is for your reference and it can't be used for any legal purpose.

Research & Development Center
Manager J. S. KIM

